

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 December 2005 (01.12.2005)

PCT

(10) International Publication Number
WO 2005/113876 A2

(51) International Patent Classification⁷: **D05B 1/00**

(21) International Application Number:
PCT/US2005/014375

(22) International Filing Date: 26 April 2005 (26.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/571,109 14 May 2004 (14.05.2004) US

(71) Applicant and

(72) Inventor: KOERNER, Ralph, J. [US/US]; P.O. Box
1320, Ramona, CA 92065 (US).

(74) Agent: FREILICH, Arthur; Freilich, Hornbaker &
Rosen, Suite 260, 9045 Corbin Avenue, Northridge, CA
91324 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM,
PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: QUILTING METHOD AND APPARATUS USING FRAME WITH MOTION DETECTOR



(57) Abstract: A frame is provided for mounting a fabric layer stack and retaining it in a substantially taut condition. The frame is supported for manually guided movement beneath a fixedly located stitch head and a detector is provided to produce signals representing the magnitude of frame translation, and thus the magnitude of stack translation. The detector signals are applied to control circuitry to actuate the stitch head at a rate related to stack translation speed. The frame is supported by bearings; wheels, slides, etc, which permit the frame to be freely manually guided across a frame supporting surface beneath the stitch head.

BEST AVAILABLE COPY

WO 2005/113876 A2